

Suspension Specifications

E90/E92/E93 Chassis 3-Series (Except M3)

Tire Pressures:

- Front 35 lbs.
- Rear 35 lbs.

Sway Bars:

- Front N/A
- Rear N/A

Shock Settings:

- Front 1-1/2 turn from full soft (for struts sold prior to 9/21/09)
- Front 1-1/4 turn from full soft (for struts sold on/after 9/21/09)
- Rear 1-1/2 turn from full soft (for non-externally adjustable shocks)
- Rear 1-1/4 turn from full soft (for shocks with external adjustment at top of shock shaft)

NOTE: All Dinan Suspension Alignments Are Done With Full Fuel Tanks And No Weight Inside The Vehicle. Vehicles equipped with Dinan's Low Compliance Bushing Kit require different alignment settings. Contact Dinan for details.

Stage 1 and 2:

Front:		Tol.
Camber	-0.6°	± 0.5°
Caster	6.5°	± 0.5°
Total Toe	0.17°	± 0.13°
Rear:		
Camber	-1.6°	± 0.4°
Total Toe	0.23°	± 0.17°

Stage 3:

Front:		Tol.
Camber	-1.1°	± 0.5°
Caster	6.5°	± 0.5°
Total Toe	0.17°	± 0.13°
Rear:		
Camber	-1.8°	± 0.4°
Total Toe	0.23°	± 0.17°