

INSTALLATION INSTRUCTIONS

Thank you for purchasing genuine Design Engineering, Inc. products. Be sure to always wear the proper safety equipment when installing any DEI product. Design Engineering Inc. WILL NOT BE HELD LIABLE FOR IMPROPER INSTALLATION OR USE OF THIS PRODUCT. Please follow all instructions provided. If you are unsure of any installation procedure, please contact a certified technician.

DESCRIPTION: 50296

1990-2005 NA & NB models

Mazda Miata Door Vibration Damping Kit

KIT CONTENTS:

- 4 6x12 sheets
- 2 2x24 Boom Mat Tape Strips
- Instructions

TOOLS NEEDED:

Panel removal tool

Straight blade and Philips screwdriver

Ratchet and metric socket set

Scissors or utility knife

SAFETY:

Safety glasses

Gloves

NOTE OF CAUTION: Wear eye and hand protection when installing all materials.

OVERVIEW: This kit controls noise and vibration on the doors on 1990-2005 Mazda Miata NA & NB models

Installation

STEP 1. Remove your door panel.

STEP 2. Clean area before applying each sheet.

STEP 3. Place the two sheets of Boom Mat in a clear area inside the door.

STEP 4. Use the Boom Mat tape to fill in any clear areas remaining. Repeat for other door.



NOTE: Diagram is for approximate location for applying material. The material is to be placed against the outter door skin. Make sure material does not interfere with normal window or door operation.